

Fittings / LED Floodlights


Skyline Virtus 150/225/300W Wattage Switchable Asymmetric Floodlight - 4000K



Designed and engineered in the UK specifically to meet the requirements for sports lighting and to reduce light pollution levels. The Skyline Virtus is a high specification floodlight, wattage switchable as standard with a 50,000 hour lifespan, 7 year warranty and 2 year on site warranty.

- Wattage Switchable.
- Perfect for sports, building facade's, landscape, security & car park lighting.
- Asymmetric distribution, low light pollution.
- Aerodynamic, streamlined design for reduced windage.
- Air pressure equalisation feature to eliminate capillary effect.
- Nichia GRT-V1 LED.
- Surge protected 10,000V.
- Fully encapsulated IP54 TUV certified driver.
- Supplied pre-flexed (1.5M).
- Robust construction, supplied with standard universal mounting bracket.

Technical Specification



	50/75/100W	150/225/300W	100/225/300W
A	353mm	447mm	495mm
B	287mm	359mm	405mm
C	65mm	75mm	75mm

Product Code 11491

Reference

Guarantee	7 Years
EAN	5013588114910
Commodity Code	9405423990
Country of Origin	CN
UNSPSC Code	39111626

Technical Specification

Volts (V)	110/240
Watts (W)	150/225/300
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	22400-46050
Life Hours	50000
Energy Rating	D
CRI (ra)	80
Switching Cycles	100000
Frequency (Hz)	50/60
LED Drive Current	132mA
Energy Consumption (kWh/1000h)	300
IP Rating	IP66
Impact Protection	IK8

Dimensions

Height (mm)	495
Width (mm)	417
Depth (mm)	75

Packaging Information

Single Carton Height (mm)	525
Single Carton Width (mm)	450
Single Carton Depth (mm)	115
Single Carton Weight (kg)	7.1
Individual Volume	0.02717
Outer Box Qty	1
Outer Box Height (mm)	525
Outer Box Width (mm)	450
Outer Box Depth (mm)	115
Outer Box Weight (kg)	7.4